

# Research on Impacts of Increasing Water Supply Guarantee for Agriculture in Dry Season to Hydraulic Works Operation in Northern Delta in Vietnam

Hoang Chi Linh<sup>1</sup>, Le Quang Vinh<sup>2</sup>  
Yamada TADASHI<sup>3</sup>

<sup>1</sup>Chuo University

(1-13-27 Kasuga, Bunkyo-ku, Tokyo 112-8551.Japan)

E-mail: [a17.afp8@g.chuo-u.ac.jp](mailto:a17.afp8@g.chuo-u.ac.jp)

<sup>2</sup>The Center for Water Research and Engineering Application, Thuy Loi University

(175 Tay Son, Dong Da, Hanoi.Vietnam)

E-mail: [lequangvinh.cra@wru.vn](mailto:lequangvinh.cra@wru.vn)

<sup>3</sup>Fellow Member of JSCE, Professor, Department of Civil and Environmental Engineering Department

(1-13-27 Kasuga, Bunkyo-ku, Tokyo 112-8551.Japan)

E-mail: [yamada@civil.chuo-u.ac.jp](mailto:yamada@civil.chuo-u.ac.jp)

Over 50 years, irrigation systems for agriculture in Vietnam were designed with a water supply guarantee not more than 75%. According to Vietnam standard 285:2002: Hydraulic works - The basic stipulation for design, stipulates that hydraulic works are designed to ensure water supply guarantee for irrigation is 75% and for living is from 80% to 95%. Guarantee of water supply, especially during dry season, depending on capacity of incoming water sources, capacity of hydraulic works to be built and will be built - is a problem that there is no scientific research so far. On the other hand, in case of sufficient water sources, the impact of increasing the water supply guarantee for agriculture and irrigation operation is also a major issue that has not been considered. This research is very necessary, with a great socio-economic significance.

**Key Words :** *water supply guarantee, water demand, water balance, Red river delta.*

## 1. INTRODUCTION


Over 50 years, irrigation systems for agriculture in Vietnam were designed with a water supply guarantee which is not more than 75%. According to Vietnam standard 285: 2002: Hydraulic works - The basic stipulation for design, stipulates that Hydraulic works are designed to ensure water supply guarantee for irrigation is 75% and for living is 80% to 95%.

Nowadays, land area for agriculture in Vietnam in general and in Red River delta region in particular is declining due to demand of industrial land, residential land, urbanized land .... At the same time, water demand for agricultural development in direction of commodity production and modernization of agriculture, diversification of agricultural production forms and increase of crop productivity needs to be paid attention; As a result, water supply for agriculture must be more and more stable. According to reference in agricultural field, irrigation water supply in Vietnam with frequency of 75% is low and not suitable for actual development requirement, it is definitely

necessary to study about increasing the water supply guarantee to higher level.

On March 6<sup>th</sup>, 2009, Ministry of Agriculture and Rural Development issued Official Letter - Technical guidance on Canal solidification in accordance to guideline of the Government which stipulates the water supply guarantee for agriculture is 85%.

Increasing the guarantee of water supply for agriculture is an urgent requirement. However, the guarantee of water supply, especially during dry season, depends on capacity of incoming water sources, capacity of the hydraulic works to be built and will be built - is a problem that there is no scientific research. On the other hand, in case of sufficient water sources, impact of increasing the water supply guarantee for agriculture and irrigation operation is also a major issue that has not been considered. This is an important basis to propose the research: " Research on impacts of increasing water supply guarantee for agriculture in dry season to hydraulic works operation in the Northern Delta in Vietnam" . This research is very necessary, with a great socio-economic significance.



**Fig. 1** Bac Hung Hai Irrigation system.

## 2. TYPICAL RESEARCH AREA

Bac Hung Hai is one of the most systematic urbanization and industrialization area in Red river delta, with large industrial zones. The process of urbanization and industrialization has led to a steady change of water demand in the region over years.

Moreover, Bac Hung Hai is the largest annual rainfall variation in the Northern Delta. The largest difference of rainfall between  $P=75\%$  and  $P=85\%$  at Hung Yen station is 14.0%, Thai Binh station is 12.53%. Therefore, this region also has the greatest impact on water demand when the guarantee of irrigation is increased.

For the reasons mentioned above, this research will focus on Bac Hung Hai irrigation system.

Bac Hung Hai irrigation system is surrounded by 4 large rivers: Duong river, Thai Binh river, Red river, Luoc river. Total area of irrigation system is 200.230 ha. Some main hydraulic works in Bac Hung Hai irrigation system: Xuan Quan Intake (built in 1959), Bao Dap Intake (built in 1959), Cau Xe Intake (built in 1969), An Tho (built in 1977).

## 3. RESEARCH METHODOLOGY

Calculate the water supply requirement for agriculture at the guarantee of 75% and 85%, and for other water users

as defined in Vietnam standard 285: 2002 Hydraulic works in the Northern Delta at present and forecast to until 2020.

Using the results of calculating amount of water in the Northern Delta by Institute of Water Resources Planning, calculate balance between water resources and water supply requirement for agriculture.

Amount of water for agriculture is calculated based on balance equation written in a period of time per unit area. Usually the period is one day, one week, half a month, one month or one crop, and the unit area is usually 1 hectare. General form of water balance equation:

$$m_i = W_{out} - W_{in} \pm \Delta W \quad (1)$$

$m_i$ : amount of water required for crop during the  $i$  period (mm/day).

$W_{out}$ : amount of water is out from the field during  $i$  period.

$$W_{out} = ET_{crop} + P_{erc} + L_{prep} \quad (2)$$

$ET_{crop}$ : evaporation in the  $i$  period (mm/day).

$P_{erc}$ : amount of water leaks into aquifer and canal during  $i$  period (mm/day).

$L_{prep}$ : amount of water for soil preparation (mm/day).

$W_{in}$ : amount of water goes to the field during  $i$  period (mm/day).

3

**Table 1** Water balance of Bac Hung Hai irrigation system in 2010.

No	Items	Unit	P=75%	P=85%
<b>1</b>	<b>Water demand</b>			
	Flow of Water Demand	m <sup>3</sup> /s	131,94	133,46
	Volume of Water Demand	10 <sup>6</sup> m <sup>3</sup>	319,19	322,87
<b>2</b>	<b>Incoming water</b>			
	Flow of Water through Intake	m <sup>3</sup> /s	74,0	71,0
	Volume of Water through Intake	10 <sup>6</sup> m <sup>3</sup>	179,20	171,76
<b>3</b>	<b>Water balance</b>			
	Flow	m <sup>3</sup> /s	-57,94	-62,46
	Volume	10 <sup>6</sup> m <sup>3</sup>	-140,17	-151,10

**Table 2** Water balance of Bac Hung Hai irrigation system in 2020.

No	Items	Unit	P=75%	P=85%
<b>1</b>	<b>Water demand</b>			
	Flow of Water Demand	m <sup>3</sup> /s	123,81	125,11
	Volume of Water Demand	10 <sup>6</sup> m <sup>3</sup>	299,52	302,67
<b>2</b>	<b>Incoming water</b>			
	Flow of Water through Intake	m <sup>3</sup> /s	93,0	90,0
	Volume of Water through Intake	10 <sup>6</sup> m <sup>3</sup>	224,99	217,73
<b>3</b>	<b>Water balance</b>			
	Flow	m <sup>3</sup> /s	-50,81	-35,11
	Volume	10 <sup>6</sup> m <sup>3</sup>	-74,54	-84,94


$b$ : width of the intake,  $b = 19$  (m).

$H_o$ : upstream water level of Xuan Quan intake (m).


$h_n$ : downstream water level of Xuan Quan intake (m).

Calculation result as table 1, table 2:


For Bac Hung Hai irrigation system, it can be seen from the Figure 1 that when irrigation water guarantee is increased from  $P = 75\%$  to  $P = 85\%$ , demand of water will increase slightly.



**Fig.3** Comparison chart of water demand in Bac Hung Hai irrigation system with  $P = 75\%$  and  $P = 85\%$  2010 and 2020



**Fig. 4** Comparison chart of water demand (black) and incoming water (grey) in 2010



**Fig. 5** Comparison chart of water demand (black) and incoming water (grey) in 2020

In February 2010, for  $P = 75\%$ , water demand of the system was 131.94 m<sup>3</sup>/s; for  $P = 85\%$ , water demand of the

system was 133,46 m<sup>3</sup>/s. The rate of increase of  $P = 85\%$  compared to  $P = 75\%$  is 1.15%.

In February 2020, for  $P = 75\%$ , water demand of the system was 123.81 m<sup>3</sup>/s; for  $P = 85\%$ , water demand of the system was 125,11 m<sup>3</sup>/s. The rate of increase of  $P = 85\%$  compared to  $P = 75\%$  is 1.05%.

Up to 2020, agricultural land area is declining, while the demand of water for agriculture accounts for a large proportion. Therefore, total water demand of whole system by 2020 is reduced compared to the current period..

In 2010:

+  $P = 75\%$ , total water demand is 131.94 m<sup>3</sup>/s; flow through Xuan Quan intake is only 74,0 m<sup>3</sup>/s (56,09%), lacking of is 94 m<sup>3</sup>/s (account for 43.91%).

+  $P = 85\%$ , total water demand increases to 133.46 m<sup>3</sup>/s, flow through Xuan Quan intake is only 71.0 m<sup>3</sup>/s (53.2%), lacking of 62.46 m<sup>3</sup>/s (account for 46.80%).

In 2020:

+  $P = 75\%$ , total water demand is 123.81 m<sup>3</sup>/s, flow through Xuan Quan intake is only 93.0 m<sup>3</sup>/s (only 75.12%), lacking of is 81 m<sup>3</sup>/s (account for 24.88%).

+  $P = 85\%$ , total water demand increases to 125,11 m<sup>3</sup>/s, flow through Xuan Quan intake is only 90,0 m<sup>3</sup>/s (71.94%), lacking of is 35.11 m<sup>3</sup>/s (account for 28.06%).

Therefore, demand of water in the current period and 2020 of Bac Hung Hai irrigation system does not sufficiently meet flow through the Xuan Quan intake.

In Northern Delta, at the present, the main hydraulic works taking water from Red River and Thai Binh River are designed and operated with guarantee  $P = 75\%$ . Therefore, when irrigation water guarantee is increased to  $P = 85\%$ , these works will not ensure sufficiently water supply for irrigation systems.

#### **4. SOME ADVICES FOR IMPROVING WATER SUPPLY REQUIREMENT**

##### **(1) When water source meets water supply requirement**

Renovation and repair in order to increase scale of hydraulic works and additionally build new ones to ensure that water is taken into the system as required.

For gravity irrigation areas, due to low water level in the systems, it is impossible to ensure gravity irrigation. Researching and constructing additional pumping stations will be done.

Change operation procedures of system to match the increase of guarantee. As soon as water is taken before

irrigation period, and alternated irrigation should be applied.

##### **(2) When water source does not meet water supply requirement**

Enhance normal capacity of upstream reservoirs, maintain the designed water level in Hanoi at 2.5m to meet requirement.

Change kind of plant in accordance to situation of incoming water source to the system.

Use construction measures in each irrigation area, store water during periods of excess water to use for periods of lacking water. Such as storage of water in ponds, lakes, canal systems.

#### **5. GENERAL ACCESSMENT**

When increasing irrigation water guarantee, demand of water does not increase significantly. As a result, irrigation guarantee does not significantly affect operation of hydraulic works in water supply for irrigation.

The current high demand of water is attributed to factors such as the area of agricultural and industrial land, as well as urbanization, population growth, livestock and aquaculture development... and increase of water use standards.

The water level in the Red River and Thai Binh River system is very complicated in the current period. This leads to not take enough water from hydraulic works, especially the gravity irrigation intakes.

Irrigation systems in the Northern Delta are directly affected by Red River system and Thai Binh River system. For deep-lying areas that is not affected by tidal regime, when water level is low, it is difficult to take water for gravity irrigation, and often fail to meet water supply requirement within the prescribed time. Measures such as rehabilitation, construction of more focal works, improvement of in-field canals, and addition of pumping stations on field should be undertaken to ensure irrigation of cultivated area to an increased guarantee. For the areas affected by tide regime, it is possible to take advantage of the tide to take water into the system, but we have to change operation mode. Take advantage of tide to take water, store water in the system, and use when the water source is scarce.

#### **REFERENCES**

- 1) Le Quang Vinh, Le Thi Thanh Thuy: Overview of current status of surface water drainage in Northern Delta 2008.
- 2) Pham Xuan Su: Results of study on operation of large reservoirs for

- integrated use and evaluation of actual conditions for operation of irrigation works in Red River basin 2009.
- 3) Pham Ngoc Hai, Tong Duc Khang, Bui Hieu, Pham Viet Hoa: Irrigation Planning and Design - Volume 1. 2006.
  - 4) Pham Viet Hoa: Water supply demand of users. 2010.
  - 5) Ngo Dinh Tuan. Scientific basis and technological solutions for sustainable development of Red River basin 2007.
  - 6) Institute of Irrigation Planning: Overview of water use in Red River-Thai Binh River basin.
  - 7) Truong Trong Luat: Evaluate the change in specifications, extent to which the difference between actual requirements and existing design standards.
  - 8) Le Hong Tuan: Calculation of water balance for the entire Red River basin.
  - 9) Institute of Irrigation Planning: Investigation and assessment of current status of water sources for spring and summer crop production in midland and Red River Delta 2007.
  - 10) Vietnam standard 285-2002: Hydraulic works-The basic stipulation for design.
  - 11) Vietnam standard 4454-1987: Planning for construction of residential areas in communes, cooperatives- Design Standard.
  - 12) Vietnam standard 4449-1987: Urban works planning – Design Standard.