


CALCULATIONS FOR

靜岡縣清水港陸上設備巴川鐵道橋設計算書

昭和四年三月

CALCULATIONS FOR

*40 ft. Lift Bridge for Shizuoka Ken  
Design of Tower.*




Dead Load of moving span.  
 Weight of Structure 20.0 tons.  
 " " track  $44 @ 200 = 8800 = 4.0$   
 Operator's houses  $2 @ 2.0 \text{ tons} = 4.0$   
 machinery = 5.0

33.0 tons or 74,000 # (37,000 # for one tower)

Counter weight Taking 95% of the above weight or  $33 \times .95 = 31.4 \text{ tons}$  or 70,000 #  
 volume of counter weight (35,000 # for one tower)  
 use punch scrap concrete, 225 #/cu ft.  
 $70,000 \div 225 = 310 \text{ cu ft}$  (155 cu ft for one tower).

CALCULATIONS FOR

40 ft Lift Bridge for Shizuoka Ken.  
Weight of Tower Frame.



Main post.		Average length		
8 Ls	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	230'	@ 8.5	= 1,564
2 Pls.	$15 \times \frac{3}{8}$	230	@ 19.13	= 880
1 Pl.	$11\frac{1}{2} \times \frac{3}{8}$	230	@ 14.66	= 336
				<u>2780 * 2 = 5560 *</u>

Sub post.		Average length		
4 Ls	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	220'	@ 8.5	= 748
1 Pl.	$12 \times \frac{3}{8}$	220	@ 15.3	= 337
				<u>1085 * 2 = 2170 *</u>

Strut		Average length		
4 Ls	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	17.5'	@ 8.5	= 425
Bracing		Average length		
2 x 2 Ls	$5 \times 3\frac{1}{2} \times \frac{3}{8}$	10.0'	@ 10.4	= 416
2 x 2 Ls	"	4.5'	@ "	= 188
1 x 2 Ls	"	6.0'	@ "	= 125
				<u>729</u>
				<u>8884</u>

Rivet heads and miscellaneous details say 35% =  $\frac{3116}{12000} *$


Shoos and anchor Bolts say  $\frac{1000}{1600}$   
Sheaves and Bearings 2 @ 800 =  $\frac{1600}{14600} *$

Stress in post.

Load on main post	say 5800 *	} 7300	15% impact
" " Sub "	say 1500 *		
Load from lift span	$37000 \div 2 = 18500$		2800
" " Counter wt.	$35000 \div 2 = 17500$		2600
wt. of tower	$\frac{5800}{41800}$		<u>5400</u>


15% impact for moving parts  $\frac{5400}{47200} *$   
Total load on one post.  $\frac{47200}{14000} = 3.37$  in sq.

Section assumed.



8 Ls	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	= 8 x 2.48 = 19.84	- 12 x 3.75 = 15.34
2 Pls	$15 \times \frac{3}{8}$	= 11.25	- 8 x 3.75 = 8.25
1 Pl.	$11\frac{1}{2} \times \frac{3}{8}$	= 4.31	- 2 x 3.75 = 3.56
		<u>35.40</u> in sq.	<u>27.15</u> in sq.

Transverse Seismic or wind stress.



Acceleration of earthquake assumed  $2500 \text{ mm/sec}^2$  or  $k=0.25$   
Seismic force due to  
Counter wt.  $35000 \times 0.25 = 8500$   
Tower  $11600 \times 0.25 = 2900$   
11400 \*


Wind pressure assumed at  $300 \text{ kg/m}^2$  or 60%  
Exposed area of lift span =  $4.7 \times 2 \times 22 = 202$   
Wind pressure due to lift span =  $202 \times 60 = 12100$   
" " Tower  $1.5 \times 24 \times 60 = 2280$   
14380 \*

Wind stress governs.

CALCULATIONS FOR

40 ft. lift span for Shizuoka Ken.

Transverse wind stress on tower frame.



$$H = H' = \frac{R}{2} = \frac{14300}{2} = 7150^*$$

$$V = -V' = \frac{R(h - \frac{d}{2})}{S} = \frac{14300(21.3 - 6.65)}{16} = 13100^*$$

Point of contra-flexure

$$y_0 = \frac{d}{2} \left( \frac{d+2b}{2d+h} \right) = \frac{13.3}{2} \left( \frac{13.3+42.6}{26.6+21.3} \right) = 7.76' \text{ above base.}$$


$$M_B = -M_A = H y_0 = 7150 \times 7.76 = 55,500 \text{ }^*$$

$$M_D = 7150 \times 5.54 = 39,600 \text{ }^*$$

$$HG = \frac{7150 \times 5.54}{8} = -4,950^*$$

$$GF = +4,950 + 14,300 = +19,250^*$$

$$GD = -GC = \frac{(4,950 + 19,250) \times 1.414}{2} = \frac{34,200}{2} = 17,100^*$$




Longitudinal seismic stress on tower bent.

$$\text{Seismic force due to counter wt. and tower} = \frac{11400}{2} = 5700^* \text{ on one side}$$

$$V = -V' = \frac{5700 \times 20.25}{2.83} = 40,800^*$$

$$H = H' = \frac{5700}{2} = 2,850^*$$



Summary for stresses.

	Reaction V	Reaction H	Stress in member			moment	
			HG	GF	DG + GC	M <sub>A</sub> + M <sub>B</sub>	M <sub>C</sub> + M <sub>D</sub>
Dead Load Stresses	47200	—	—	—	—	—	—
Wind stresses	13100	7150	4950	19250	17100	55500	39600
Seismic stresses	40800	* 5700	* 3950	* 15350	* 13600	* 44300	* 31600
DL + W.L	60300	7150	4950	19250	17100	55500	39600
DL + S.L	88000	* 5700	* 3950	* 15350	* 13600	* 44300	* 31600
DL + W.L + S.L	148300	12850	8900	34600	30700	99800	71200
min	-6700						

Note mark \* indicates transverse seismic stresses (by proportion).

Load on pier

Dead Load main post 2 @ 41800 = 83600

Sub post 2 @ 1500 = 3000


Live Load (Cooper E40) 2 @ 78000 = 156000

242600\* on one pier

CALCULATIONS FOR

40 Ft. Light span for Shizuoka Ken.


Section for main post.



max. load during wind 60300#  $M_A = 55500 \text{#}$   
 , during wind + earthquake 148300  $M_A = 99800$   
 moment of inertia about Y-Y axis  
 4LS  $3\frac{1}{2} \cdot 3\frac{1}{2} \cdot \frac{3}{8} = 44.248 = 992 \text{#}$   $29.4 + 992 \cdot 7.385^2 = 553$   
 4LS " " " = 992  $29.4 + 992 \cdot 4.99^2 = 259$   
 2Pls  $15 \cdot \frac{3}{8} = 11.25$   $11.25 \cdot 6.19^2 = 431$   
 1Pl.  $11\frac{1}{2} \cdot \frac{3}{8} = 4.31$   $\frac{48}{1291 \text{#}}$   
 $\frac{4.31}{35.40 \text{#}}$   
 Radius of gyration  $R_y = \sqrt{\frac{1291}{35.4}} = 6.04 \text{#}$   $\frac{L}{R_y} = \frac{21.3 \cdot 12}{6.04} = 42.3$


Y

Stress during wind =  $\frac{60300}{35.4} \pm \frac{55500 \cdot 12 \cdot 9.875}{1291} = 1705 \pm 5090 = 6745 \text{#/in}^2$   
 $\approx 3385 \text{#}$   
 Stress during wind + earthquake =  $\frac{148300}{35.4} \pm \frac{99800 \cdot 12 \cdot 9.875}{1291} = 4210 \pm 9160 = 13370 \text{#/in}^2$   
 $\approx 4950 \text{#}$   
 Allowable stress =  $1200 - 5 \frac{L}{r} = 1200 - 5 \cdot 42.3 = 989 \text{#/in}^2 = 14000 \text{#}$   
 allowable stress during wind =  $14000 \cdot 1.25 = 17500 \text{#}$   
 " " " wind + earthquake =  $14000 \cdot 1.4 = 19600 \text{#}$  ok  
 Unit stress shear =  $12850 \div 4.31 = 2980 \text{#}$  ok  
 Use same section throughout the column.  
 Anchor Bolts 4 Bolts




Tension on 2 Bolts  $T = -\frac{M_a}{2a} + \frac{P-V}{2} = -\frac{99800 \cdot 12}{18.5} - \frac{6700}{2} = 68100 \text{#}$   
 Tension for one bolt =  $\frac{68100}{2} = 34050 \text{#}$   
 Area req'd =  $\frac{34050}{16000 \cdot 1.25} = 1.52 \text{#}$   
 Use 4 -  $1\frac{5}{8} \text{#}$  bolts 310 long

Sub Column



Moment of inertia about X-axis.  
 4LS  $3\frac{1}{2} \cdot 3\frac{1}{2} \cdot \frac{3}{8} = 992$   $29.4 + 992 \cdot 4.99^2 = 259$   
 1Pl.  $11\frac{1}{2} \cdot \frac{3}{8} = 4.31$   $\frac{48}{14723 \text{#} = 10.375 = 10.48 \text{#}}$   
 Radius of gyration  $R_x = \sqrt{\frac{307}{14723}} = 4.65 \text{#}$   
 $\frac{L}{R_x} = \frac{21.5 \cdot 12}{4.65} = 55.4$

Unit tension =  $\frac{40800}{10.48} = 3890 \text{#}$  ok




Unit comp. =  $\frac{40800}{14723} = 2870 \text{#}$  ok

Anchor bolts

Area req'd =  $\frac{40800}{16000 \cdot 1.25} = 2.04 \text{#}$  for 2 bolts

Use 2 -  $1\frac{3}{8} \text{#}$  bolts 2'6"

Section of Top Struts








4LS  $3\frac{1}{2} \cdot 3\frac{1}{2} \cdot \frac{3}{8} = 992 \text{#}$   $Stress = 34600 \text{#}$   
 Unit stress =  $\frac{34600}{992} = 3490 \text{#}$  ok

moment of inertia 4LS  $29.4 + 992 \cdot 6.74^2 = 463 \text{#}$   
 $I = \sqrt{\frac{463}{992}} = 6.82 \text{#}$   
 $\frac{L}{r} = \frac{16 \cdot 12}{6.82} = 28.2 \text{#}$  ok

Use 8 -  $7/8 \text{#}$  rivets or more

CALCULATIONS FOR

40 ft. lift span for Shizuoka Ken.

<p>Struts in diagonal</p> 	<p>30700 # Tor C  <math>ZL5\ 5 \times 3\frac{1}{2} \times \frac{3}{8} = 6.10 \times 9 - 1.50 = 4.6 \text{ in}</math>  Unit stress = <math>\frac{30700}{4.6} = 6680 \text{ #/in}^2</math> T OK  or <math>= \frac{30700}{6.1} = 5030 \text{ #/in}^2</math> C OK  <math>f_x = 1.6 \text{ in}</math> <math>l/r = \frac{6 \times 12}{1.6} = 45</math> OK  Use 8 - <math>\frac{7}{8}</math>" rivets</p>										
<p>Flange area of main girder for the additional dead load due to Operator's houses and Machinery.</p>  <p>Operator's house Machineries</p>	<p>2 tons or 4480 # at center of span assumed. (for one girder)  Reaction = 2240 #  moment = <math>2240 \times 18.17 = 40,700 \text{ #ft}</math>  2.5 tons or 5600 # distributed over span.  or <math>w = \frac{5600}{42.33} = 133 \text{ # per lin. ft. of span}</math></p>										
 <p>Increased wt. of structural steel etc.</p> 	<p>moment = <math>\frac{133 \times 42.33^2}{8} = 29,800 \text{ #ft}</math>  1.0 tons or 2240 # distributed over span.  or <math>w = \frac{2240}{42.33} = 53 \text{ # per lin. ft. of span}</math>  moment = <math>\frac{53 \times 42.33^2}{8} = 11,900 \text{ #ft}</math></p>										
<p>Summary of moment</p> <table border="0"> <tr> <td>Operating house</td> <td>40,700</td> </tr> <tr> <td>machineries</td> <td>29,800</td> </tr> <tr> <td>Steel increased</td> <td>11,900</td> </tr> <tr> <td></td> <td><u>82,400 #ft</u></td> </tr> </table>	Operating house	40,700	machineries	29,800	Steel increased	11,900		<u>82,400 #ft</u>			
Operating house	40,700										
machineries	29,800										
Steel increased	11,900										
	<u>82,400 #ft</u>										
<p>Flange section (Standard.)</p> 	<p>Z cov. pls. <math>13\frac{1}{2} \times \frac{3}{8} = 10.1 \times .375 = 3.79</math>  Z L5 <math>6 \times 6 \times \frac{1}{2} = 11.5 \times 2.43 = 27.90</math>  21.6 <math>\times 1.47 = 31.69</math></p>										
	<p>Effective depth of girder = <math>58.0 - 1.47 \times 2 = 55.06 \text{ in}</math>  Flange area to be increased = <math>\frac{82400 \times 12}{55.06 \times 16000} = 1.12 \text{ in}^2</math> at center of span.  <math>\frac{1}{8}</math>" of cov. pl. = <math>13.5 \times \frac{1}{8} = 1.69 \text{ in}^2</math>  Use ZL5 <math>6 \times 6 \times \frac{1}{2}</math>  Z cov. pls. <math>13\frac{1}{2} \times \frac{7}{16}</math> instead of Z cov. pls. <math>13\frac{1}{2} \times \frac{3}{8}</math>.  Cover plate length shall be added <math>\frac{1.12 \times 16000}{6010} = 3</math> rivets  use 4 extra rivets or 9" elongated on both sides.</p>										

CALCULATIONS FOR

40 ft. Lift Span for Shizuoka Ken

Design of Operating machinery  
Weight of lift

Lift span	20	assumed
Track	4	"
Operator's house	4	"
Machine part	5	
	<u>33</u>	
Counter weight	$33 \times 95 = 31.4$	
	<u>64.4</u>	say 65 tons.

Span. 42' 4" C.to C. Bearings  
Lift 12' 6"

Power required for vertical Lift span

1. unbalanced loads.

$$33 \times 0.5 \times 2240 = 1.65 \times 2240 = 3700 \#$$

2. friction between guides and tracks.

wind pressure 30 #/sq. ft.

$$\text{total wind load } 42.5 \times 4.75 \times 30 = 6100 \#$$

$$\text{friction } 6100 \times 0.15 = 920 \#$$

3. Vertical wind loads.

$$\text{wind pressure } 3 \#/\text{sq. ft. on the horizontal projection}$$

$$\text{loads} = 3 \times 42.5 \times 13 \times \frac{1}{2} = 830 \#$$

4. Snow loads.

$$1 \#/\text{sq. ft. assumed}$$

$$\text{load} = 1 \times 42.5 \times 13 \times \frac{1}{2} = 280 \#$$

5 Force required for accelerating the span

$$F_1 = \frac{Wa}{g}$$

where  $F_1$  = force required in lbs.

$$W = \text{total weight of all moving load } 65 \times 2240 = 135,600 \#$$

$a$  = acceleration in ft. per sec.<sup>2</sup>

operating time of lift 12' 6" / min 20 sec.

acceleration time 20 sec.

retardation time 20 sec.

uniform motion 40 sec.

$$\text{uniform speed } \frac{12.5}{\frac{20}{2} + 40 + \frac{20}{2}} = \frac{12.5}{60} = 0.208 \# \text{ per sec.}$$

$$a = \frac{0.208}{20} = 0.01 \text{ ft. per sec.}^2$$

then

$$F_1 = \frac{135,600 \times 0.01}{32.2} = 42 \# \text{ say } 50 \#$$

$$\text{Total load} = 5,780 \# \text{ take } 5,800 \#$$

6. Friction of gears.

assume 2 spur gears and 1 worm gear.

$$\text{Total efficiency} = .93 \times .93 \times .65 = 56 \%$$

7. Force reqd. to bend the cables on and off of sheaves and drum.

$$\text{Total efficiency} = 95 \times 95 = 90 \%$$

$$\text{Power } P = \frac{5800 \times 12.5}{33,000 \times .56 \times .9} = \frac{144,000}{33,000} = 4.4 \text{ H.P.}$$

Take 7.5 H.P.

CALCULATIONS FOR

Material list for 40'-0" lift span, Shizuoka-Ken

No.	Description	Section	Length	Total wt #
<b>主桁 for lift span</b>				
8	蓋鉄	13 $\frac{1}{2}$ " x 7"	16 $\frac{1}{4}$	2,586
4	"	"	23 $\frac{3}{8}$	1,871
4	添接鉄	"	3 $\frac{7}{8}$	291
8	山形	6 x 6 x $\frac{5}{8}$	43 $\frac{6}{8}$	6,821
4	腹鉄	56 x $\frac{3}{8}$	21 $\frac{9}{8}$	6,212
8	添接鉄	5 $\frac{1}{2}$ x $\frac{3}{8}$	2 $\frac{4}{8}$	131
4	"	13 x $\frac{3}{8}$	3 $\frac{8}{8}$	245
28	補剛材	5 x 3 $\frac{1}{2}$ x $\frac{3}{8}$	4 $\frac{7}{8}$	1,347
40	"	4 x 3 $\frac{1}{2}$ x $\frac{3}{8}$	4 $\frac{8}{8}$	1,699
8	填材	7 x $\frac{1}{2}$	3 $\frac{8}{8}$	351
12	"	3 $\frac{1}{2}$ x $\frac{1}{2}$	3 $\frac{8}{8}$	263
3440	銼頭 (工場鉄) 径 7/8"			663
208	缶 (現場鉄)			40
				<u>22,520</u>
<b>継桁</b>				
12	山形	4 x 4 x 7/10	11 $\frac{6}{8}$	1,559
12	"	"	12 $\frac{1}{8}$	1,646
6	腹鉄	25 $\frac{1}{2}$ x $\frac{3}{8}$	9 $\frac{5}{8}$	1,850
12	鉄	16 x $\frac{3}{8}$	3 $\frac{11}{8}$	782
48	添接鉄	3 $\frac{1}{2}$ x $\frac{3}{8}$	1 $\frac{6}{8}$	326
24	"	12 $\frac{1}{2}$ x $\frac{3}{8}$	1 $\frac{5}{8}$	539
24	填材	10 x 7/16	1 $\frac{5}{8}$	513
24	補剛材	6 x 3 $\frac{1}{2}$ x $\frac{3}{8}$	2 $\frac{0}{8}$	576
12	隅束	3 $\frac{1}{2}$ x 3 $\frac{1}{2}$ x $\frac{3}{8}$	1 $\frac{6}{8}$	157
12	"	"	2 $\frac{10}{8}$	289
12	連結山形	5 x 3 $\frac{1}{2}$ x $\frac{3}{8}$	1 $\frac{1}{2}$	140
12	填材	3 $\frac{1}{2}$ x $\frac{3}{8}$	0 $\frac{6}{8}$	30
1650	銼頭 (工場鉄) 径 7/8"			319
432	缶 (現場鉄)			83
				<u>8,809</u>
<b>縦桁</b>				
10	山形	3 $\frac{1}{2}$ x 3 $\frac{1}{2}$ x $\frac{3}{8}$	4 $\frac{10}{8}$	664
10	"	"	5 $\frac{10}{8}$	795
8	鉄	15 x 7/10	5 $\frac{10}{8}$	1,045
10	山形	6 x 6 x 7/10	0 $\frac{7}{2}$	172
1240	銼頭 (工場鉄) 径 7/8"			239
384	缶 (現場鉄)			74
				<u>2,989</u>
<b>継構</b>				
6	山形	3 $\frac{1}{2}$ x 3 x $\frac{3}{8}$	12 $\frac{4}{2}$	586
12	"	"	6 $\frac{1}{1}$	577
24	"	3 $\frac{1}{2}$ x 3 $\frac{1}{2}$ x $\frac{3}{8}$	0 $\frac{8}{8}$	136
6	鉄	7 x $\frac{3}{8}$	2 $\frac{0}{2}$	110
12	"	14 $\frac{1}{2}$ x $\frac{3}{8}$	1 $\frac{9}{2}$	398
66	銼頭 (工場鉄) 径 7/8"			13
670	缶 (現場鉄)			129
				<u>1,949</u>
				36,267

CALCULATIONS FOR

*Material list for 40'-0" lift span, Shizuoka-Ken*

NO.	Description	Section	Length	unit wt.	Total wt.
<i>Operating house &amp; Center panel of Lift span</i>					
4	ls	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	5'-11"	8.5	201.2
4	"	"	5'-6"	"	187.0
2	Web pls.	25" x $\frac{3}{8}$	5'-11"	31.88	377.3
2	ls	4" x $3\frac{1}{2} \times \frac{3}{8}$	1'-5"	9.1	25.8
4	"	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	1'-6"	8.5	51.0
2	pls.	11" x $\frac{3}{8}$	1'-2"	14.03	32.7
2	"	"	1'-0"	"	28.1
2	ls	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	6'-8"	8.5	113.3
2	pls.	15" x $\frac{3}{8}$	2'-1"	19.13	79.7
4	Lac-bars	3" x $\frac{1}{2}$	2'-11"	5.10	59.5
1	L	3" x 3" x $\frac{3}{8}$	7'-4 $\frac{1}{2}$ "	7.2	53.1
2	ls	"	3'-8"	"	52.8
1	pl.	8" x $\frac{3}{8}$	1'-5"	10.2	14.5
4	"	11" x $\frac{3}{8}$	1'-3"	14.03	70.2
2	ls	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	0'-7"	8.5	9.9
4	"	$3\frac{1}{2} \times 3 \times \frac{3}{8}$	4'-1"	7.9	129.0
2	pls	6" x $\frac{3}{8}$	1'-5 $\frac{1}{2}$ "	7.65	22.3
2	"	$8\frac{1}{2} \times \frac{3}{8}$	1'-4"	10.84	28.9
4	ls	4" x $3\frac{1}{2} \times \frac{3}{8}$	4'-10 $\frac{1}{2}$ "	9.1	177.5
4	"	4" x $3\frac{1}{2} \times \frac{3}{8}$	5'-10 $\frac{1}{2}$ "	"	213.1
2	Web pls.	23" x $\frac{3}{8}$	5'-10 $\frac{1}{2}$ "	29.33	343.4
4	ls	6" x 6" x $\frac{7}{16}$	1'-4"	17.2	91.7
2	ls	6" x $3\frac{1}{2}$	2'-3"	17.9	80.6
2	ls	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	0'-5 $\frac{1}{2}$ "	8.5	7.8
2	ls	6" x $3\frac{1}{2}$	6'-9"	17.9	241.7
1	pl.	44" x $\frac{3}{8}$	6'-9"	56.1	378.7
					<u>3070.8</u> #
					110
<i>Drum box. 4 Req'd.</i>					
3	ls	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	2'-0"	8.5	51.0
2	pls.	20" x $\frac{3}{8}$	2'-0"	25.5	102.0
1	pl.	20 $\frac{1}{2}$ " x $\frac{3}{8}$	2'-0"	26.14	52.3
2	ls	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	1'-8"	8.5	28.3
2	"	"	1'-1"	"	18.4
3	"	"	1'-2"	"	19.8
2	pls	20" x $\frac{3}{8}$	1'-9"	25.5	89.3
					<u>361.1</u> ✓
					4 ✓
					<u>1444.4</u> ✓
					40
<i>End Panel 2 Req'd.</i>					
1	ls	6" x $3\frac{1}{2}$	3'-7 $\frac{1}{2}$ "	17.9	64.9
2	ls	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	0'-5 $\frac{1}{2}$ "	8.5	7.9
4	"	6" x $3\frac{1}{2} \times \frac{3}{8}$	0'-3"	11.7	11.7
4	"	4" x $3\frac{1}{2} \times \frac{3}{8}$	5'-0 $\frac{1}{2}$ "	9.1	183.5
4	"	"	6'-1"	"	221.4
2	Web pls.	19" x $\frac{3}{8}$	6'-0"	24.23	290.8
4	ls	6" x 6" x $\frac{7}{16}$	1'-0"	17.2	68.8
2	pls.	15" x $\frac{3}{8}$	2'-0"	19.13	76.5
4	ls	6" x 4" x $\frac{3}{8}$	0'-3"	12.3	12.3
4	"	4" x $3\frac{1}{2} \times \frac{3}{8}$	0'-8 $\frac{1}{2}$ "	9.1	25.8







CALCULATIONS FOR

Material list for 40'0" lift span, Shizuoka-Ken

2	Web pl.	8 × 3/8	1" 7	10.2	32.8	
2	ls	6 × 6 × 7/16	1" 0	17.2	34.4	
2	Pls	10 1/2 × 3/8	1" 2 1/2	13.39	32.4	
2	ls	6 × 3 1/2	3" 5 1/2	17.9	123.8	
2	ls	3 1/2 × 3 1/2 × 3/8	0" 5 1/2	8.5	7.8	
1	L	6 × 4 1/2 (6 × 6) × 3/8	1" 6	14.9	22.4	
					1,210.7 ✓	
					2 ✓	
					2,433.4 ✓	60
End Floor Beam. 2 Req'd.						
2	Flg. ls	4 × 4 × 7/16	11" 6	11.3	259.9	
1	"	"	12" 1 5/8	"	137.1	
1	"	"	12" 2 5/8	"	138.1	
1	Web pl.	24 × 3/8	9" 4	30.6	285.6	
2	Fills	3 1/2 × 3/8	0" 6 1/2	4.46	5.9	
2	web pl.	17 × 3/8	4" 0	21.68	173.4	
2	ls	3 1/2 × 3 1/2 × 3/8	2" 11	8.5	49.6	
2	"	"	1" 9	"	29.8	
4	Pls.	12 1/4 × 3/8	1" 5	15.62	110.7	
4	ls	6 × 3 1/2 × 3/8	1" 11 1/2	11.7	41.6	
4	Fills	10 × 7/16	1" 5	11.88	67.3	
2	"	10 1/2 × 7/16	1" 2 3/4	15.62	38.4	
2	Fills	13 1/2 × 7/16	1" 2 3/4	20.08	49.4	
2	ls	4 × 4 × 7/16	1" 1 1/2	11.3	25.4	
2	"	"	1" 5 1/2	"	33.0	
2	Web. Pls.	17 1/2 × 3/8	3" 3	22.31	145.0	
2	ls	4 × 4 × 7/16	1" 6 1/2	11.3	34.8	
2	"	"	1" 1	"	24.5	
2	"	"	3" 3	"	73.5	
2	Tension pl.	14 × 1/2	1" 5 1/2	23.8	69.4	
					1,842.4 ✓	
					2 ✓	
					3,684.8 ✓	130

CALCULATIONS FOR

Material list for 400' lift span. Shizuoka-Ken

✓ Center Lock		✓ 2 Req'd.			
2	Pls	14 × ½	128½	23.8	81
2	L	6 × 3½ × 3/8	122	11.7	27
2	"	4 × 4 × 3/8	028	9.8	13
1	Pl.	14 × 3/8	128	17.85	30
1	L	6 × 3½ × 3/8	128	11.7	20
2	shim pls	6 × ½	122	10.2	24
1	"	4½ × ½	122	7.65	9
					204
					2
					<u>408</u>
Cast steel and iron (Shoes and Center lock)					
	Cast steel shoe		83.5 <sup>#</sup> × 2		167
	"		256. × 2		512
	Steel pl.		45 × 2		90
	Cast iron shoe		280 × 2		572
	Center lock (cast iron)		48 × 2		96
	" (cast steel)		74.5 × 2		149
					<u>1580</u>
Anchor bolts or bolts					
8	Anchor bolts	1½" 240 long	9.2 × 8		74
10	bolts	1" 24 "	1.48 × 10		24
8	Anchor bolts	1" 140 "	3.1 × 8		25
24	bolts	¾" 34 "	.78 × 24		19
8	Taped bolts	½" 12 "	.154 × 8		1
					<u>143</u>
(Lift girder span. Rivet head 変換) total wt. --- 49,037.4 <sup>#</sup>				=	21.877
変更部分, Rivet head --- 340.0				=	Tons.
49,377.4				=	22.043

CALCULATIONS FOR

*Material list for 40Lo" lift span, Shyokaku*

Main towers				2 Required.	
4	LS	3 1/2 x 3 1/2 x 3/8	23'-8 5/8"	8.5	806.4
12	"	"	21'-10 7/8"	"	2233.4
2	Pls	15 x 3/8	23'-8 5/8"	19.13	907.5
2	"	"	21'-10 7/8"	"	837.7
2	"	1 1/2 x 3/8	21'-10 7/8"	14.66	642.0
4	"	4.4 x 3/8	3'-9 1/4"	56.10	846.2
4	"	17 1/2 x 3/8	1'-7 1/4"	22.31	146.9
4	"	20 1/2 x 3/8	2'-3"	26.14	225.2
10	"	8 1/2 x 3/8	1'-7 1/4"	10.84	178.4
8	Lac. Bars	3 x 7/8	2'-4"	4.46	83.2
4	Washers	3 x 7/8	"	0.9	3.6
2	Pls (a)	19 1/4 x 3/8	2'-2"	25.18	109.2
2	" (b)	"	3'-5"	"	172.1
2	LS (c)	6 x 4 x 1/2	1'-7 1/4"	16.2	53.3
4	" (d)	4 x 3 x 1/2	"	11.1	73.1
4	Fills (f)	3 1/4 x 1/2	"	5.53	36.4
24	LS (g)	3 1/2 x 3 1/2 x 3/8	0'-11 1/2"	8.5	195.4
4	" (h)	6 x 4 x 1/2	1'-2 1/2"	16.2	78.3
4	" (j)	4 x 3 x 1/2	0'-8"	11.1	29.6
4	Fills (k)	3 1/4 x 1/2	0'-8"	5.53	14.8
4	" (m)	8 x 3/8	6'-4 1/4"	10.2	259.2
4	LS (n)	6 x 4 x 1/2	0'-11"	16.2	59.4
4	Fills (p)	4 1/2 x 3/8	0'-6"	5.74	11.5
2	LS (c')	6 x 4 x 1/2	1'-10"	16.2	59.4
4	Pls (r)	12 1/2 x 3/8	2'-0 1/2"	26.56	216.7
8	LS (s)	3 1/2 x 3 1/2 x 3/8	3'-9 1/4"	8.5	256.4
2	Pls (t)	15 x 3/8	3'-9 1/4"	19.13	144.3
2	" (u)	"	1'-9"	"	67.0
4	LS (v)	3 1/2 x 3 1/2 x 3/8	2'-0"	8.5	68.0
8	" (w)	"	1'-3 1/2"	"	86.4
4	" (x)	"	2'-9 1/4"	"	94.2
2	Pls (y)	15 x 3/8	2'-9 1/4"	19.13	106.0
8	LS (z)	6 x 4 x 1/2	0'-11"	16.2	118.8
4	" (a)	"	1'-2 1/2"	"	78.3
4	Fills (b)	6 x 3/8	0'-8"	7.65	20.4
4	LS	3 1/2 x 3 1/2 x 3/8	12'-4"	8.5	419.3
32	Lac. Bars	2 1/2 x 3/8	1'-7 1/2"	3.19	165.9
4	Pls (d')	22 x 3/8	2'-1"	46.75	389.5
2	"	2 1/2 x 3/8	2'-0"	28.69	114.8
2	tie Pls	15 x 3/8	"	19.13	76.5
4	"	12 x 3/8	1'-3"	15.30	76.5
32	Lac. bars	2 1/2 x 3/8	1'-8"	3.19	170.2
4	LS	5 x 3 x 3/8	9'-11"	9.8	388.7
4	Pls	11 1/2 x 3/8	1'-3"	14.66	73.3
2	"	14 1/2 x 3/8	1'-3"	18.49	46.2
4	"	12 x 3/8	2'-3"	15.30	137.7
4	LS	5 x 3 x 3/8	4'-2"	9.8	163.3
4	Pls	8 1/2 x 3/8	1'-3"	10.84	54.2
8	Lac. Bars.	2 1/2 x 3/8	1'-5 1/2"	3.19	37.2
2	LS	5 x 3 x 3/8	5'-10"	9.8	114.3
2	Pls	8 1/2 x 3/8	1'-3"	10.84	27.1
7	Lac. Bars.	2 1/2 x 3/8	1'-5 1/2"	3.19	32.6
2	LS	4 x 3 x 3/8	1'-7 1/4"	8.5	28.0
2	Pls	11 1/2 x 3/8	"	14.66	48.3
2	"	17 1/2 x 3/8	"	22.31	73.4

CALCULATIONS FOR

Material list for 40'-0" lift span, Shugokaku.

2	LB	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	0'-0 $\frac{1}{2}$ "	85	120
4	"	"	1'-0"	"	340
4	Fill.	$3 \times \frac{3}{8}$	0'-3 $\frac{1}{2}$ "	383	45
10	Pls.	$8\frac{1}{2} \times \frac{3}{8}$	1'-7 $\frac{1}{4}$ "	1084	1784
2	LB	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	1'-3"	85	213
4	Fill.	$3 \times \frac{3}{8}$	0'-3 $\frac{1}{2}$ "	383	45
					12220.4#
					2
					24440.8# or 10911 Tons
√ Side Column				√ 4- Required	
4	LB	$3\frac{1}{2} \times 3 \times \frac{3}{8}$	2'-7 $\frac{1}{2}$ "	79	6834
1	Pl.	$11\frac{1}{2} \times \frac{3}{8}$	"	14.66	317.0
2	LB	$6 \times 4 \times \frac{1}{2}$	0'-11 $\frac{1}{4}$ "	162	304
1	Fill.	$5\frac{1}{2} \times \frac{3}{8}$	1'-0 $\frac{1}{2}$ "	701	73
1	"	"	0'-6"	"	35
1	LB	$6 \times 4 \times \frac{1}{2}$	0'-5 $\frac{1}{2}$ "	162	74
2	Pls.	$13\frac{1}{2} \times \frac{3}{8}$	1'-5 $\frac{1}{2}$ "	2869	837
2	LB	$3\frac{1}{2} \times 2\frac{1}{2} \times \frac{3}{8}$	0'-11 $\frac{1}{2}$ "	72	138
1	Pl.	$12 \times \frac{3}{8}$	1'-1"	153	166
1	L.	$6 \times 4 \times \frac{1}{2}$	"	162	175
4	Pls.	$12 \times \frac{3}{8}$	"	153	663
3	"	$10 \times \frac{3}{8}$	1'-0"	1275	383
8	LB	$2\frac{1}{2} \times 2\frac{1}{2} \times \frac{3}{8}$	1'-10"	47	689
1	Pl.	$7\frac{1}{2} \times \frac{3}{8}$	"	956	175
1	L.	$6 \times 4 \times \frac{3}{8}$	2'-5 $\frac{1}{4}$ "	123	300
1	Pl.	$11 \times \frac{3}{8}$	0'-11"	1403	129
2	Pls	$8\frac{1}{2} \times \frac{3}{8}$	2'-5 $\frac{1}{4}$ "	1084	529
2	LB	$6 \times 3 @ 1449\#$	2'-1 $\frac{1}{4}$ "		610
4	LB	$6 \times 6 \times \frac{7}{16}$	0'-5"	172	287
2	Pls	$6 \times \frac{1}{2}$	0'-10"	102	170
2	LB	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	0'-11 $\frac{1}{2}$ "	85	163
1	L	$12 \times 3\frac{1}{2} @ 2610\#$	3'-3"		848
1	"	"	2'-1 $\frac{1}{4}$ "		549
1	"	"	1'-5 $\frac{1}{4}$ "		375
1	"	$9 \times 3 @ 1937\#$	1'-7"		307
2	LB	$3\frac{1}{2} \times 3\frac{1}{2} \times \frac{3}{8}$	0'-8 $\frac{1}{4}$ "	85	120
					18103
					4
					7241.2# or 3235 Tons
Anchor bolts for Columns				4 Req'd.	
1	Anchor Bolt	$1\frac{3}{8}$	3'-6"	@188	188
2	"	"	2'-0"	@113	226
6	"	"	3'-6"	@188	1128
9	Washers	$4 \times \frac{1}{2}$	0'-4"	68	208
					1750
					4
					700.0#
Total wts. of Towers				323820	
$\frac{3}{4}$ Rivet heads				1150.0	
				33,532.0 or 14,970 Tons	

CALCULATIONS FOR

Material list for 40'-0" lift span, Shizuoka-Ken

✓ Rail Joint				✓ 4 Required.	
1	Jointing Casting		@	55.0	55.0
9	Cast steel beveled washers		@	1.16	10.4
6	Lag screw $\frac{3}{8}$ " $\phi$ x 0'-6"		@	1.4	8.4
6	Bolts $\frac{3}{8}$ " $\phi$ x 0'-6 $\frac{1}{2}$ "		@	1.68	10.1
3	" " x 0'-5"		@	1.43	4.3
1	Pl. 10 x $\frac{1}{2}$ x 1'-6"			17.0	25.5
1	" 9 x $\frac{1}{2}$ x 1'-4 $\frac{1}{2}$ "			15.3	21.0
					134.7
					x 4 ✓
					538.8 or 0.241 Tons.
Counter Weight girders				✓ 2 Required	
4	LS	6 x 3 $\frac{1}{2}$ x $\frac{3}{8}$ x 16'-6"		11.7	772.2
1	Pl.	29 x $\frac{3}{8}$ " " "		36.98	510.2
24	LS	4 x 3 x 300 x 3'-5 $\frac{1}{2}$ "		6.84	567.7
6	Pls	5 $\frac{1}{2}$ x $\frac{3}{8}$ 2'-4 $\frac{1}{2}$ "		7.01	99.9
12	LS	4 x 3 x 300 1'-10"		6.84	150.5
6	Pls	5 $\frac{1}{2}$ x $\frac{3}{8}$ 2'-4 $\frac{1}{2}$ "		7.01	99.9
12	Fills	4 x $\frac{3}{8}$ 2'-5 $\frac{1}{2}$ "		5.10	150.4
8	LS	4 x 3 x 300 " "		6.84	134.5
8	"	" " 1'-10"		"	100.3
4	"	" " 2'-5 $\frac{1}{2}$ "		"	133.4
2	Pls	28 $\frac{1}{2}$ x $\frac{3}{8}$ 3'-9 $\frac{1}{2}$ "		36.34	275.6
4	"	24 x $\frac{3}{8}$ 3'-5 $\frac{5}{8}$ "		30.60	424.6
2	LS	8 x 3 2'-5"		19.30	93.3
4	LS	4 x 3 x 300 0'-6"		6.84	13.7
					3526.2
					x 2 ✓
					7052.4
					195.0
					7247.4 # or 3235 Tons.
				$\frac{3}{4}$ " Rivet heads	



CALCULATIONS FOR

*Material list for 40'-0" lift span, Shizuoka-Ken*

TOTAL WEIGHT SUMMARY FOR LIFT 40'-0" SPAN 1 Required.

	TONS.	
Main girders (1本17ト7金)	22.043	} 40.248
Towers ( " )	14.970	
Counter w/ girder ( " )	3.235	
Ladders	0.303	
Rail joint.	0.241	
	40.792	


GRAND TOTAL WEIGHT.

	TONS.
40'-0" LIFT SPAN	40.792 x 1 = 40.792
40'-0" FIXED ;	17.984 x 5 = 89.920
30'-0" " "	11.966 x 1 = 11.966
	142.678



CALCULATIONS FOR

Equalizer  $\frac{33 \text{ tons}}{4} = 8.25 \text{ tons} \times 2240 = 18,500 \text{ #}$   
 Size of cable try  $2\frac{3}{4}$  - breaking strength 26.82 tons  
 factor of safety =  $\frac{26.82}{8.25} = 3.25$  Using 2 cables - factor of safety = 6.5  
 structural steel section =  $\frac{18,500}{16,000} = 1.16 \text{ in}$  Diameter max.  $1\frac{1}{2}$  in. use  $\frac{1}{8}$  in.  $\phi$  2 pins each cable



Bending moment of pin  $\frac{18,500 \text{ #} \times 1.25}{2} = 11,562 \text{ #in}$   
 dia of pin =  $1\frac{3}{4}$  in. for 12600 lbs. max. wd. area  $\frac{1}{4}$   
 bearing area =  $1\frac{3}{4} \times 1\frac{1}{2} = 2.62$   $11,562 \div 2.62 = 4413 \text{ #/sq in}$  OK



CALCULATIONS FOR

$16 \times \frac{3}{4} \times 2.5 = 40.8 \times 2.5 = 560$ $30.6 \times 3.5 \times 2.5 = 370$		<p>75</p> <p><u>23.5</u></p> <p>79</p> <p>23.5</p>
$6 \frac{1}{2} \times \frac{5}{8} \times 0.9 \frac{1}{2} = @ 13.8 \times 1.79 = 10.9$ $2 \frac{1}{2} \times \frac{5}{16} \times 2.7 = @ 2.66 \times 2.58 = 6.9$ $4 \times 1 \times 2.46 = @ 4.25 \times 2.5 = 10.5$ $6 \times 2 \times 0.9 = @ 6.38 \times 1.75 = 4.8$	<p>24</p>	<p>31 #7</p>
	$33.1 \times 0.92 = 30.1$	

CALCULATIONS FOR

1. General Plan and Elevation of Lift man
2. Details of main guide
3. " " floor beam truss + c
4. Tower
5. " " Detail counter weight + Rope
6. ~~Detail counter weight + Rope~~
7. Tower sheaves, bearings + shaft
8. General arrangement of machinery + floor and rail
9. detail of drum + bearings + capstan + drum
10. " " worm gears
11. bearings, couplings for operating shaft
12. Common Bearings
13. ~~Details of gears~~
14. General arrangement of End locking +
15. Machinery for end locking -
16. End locking guide + roller guide left side
17. details of air buffer
18. wiring diagram

Copyright © (2004) by P.W.R.I.

All rights reserved. No part of this book may be reproduced by any means, nor transmitted, nor translated into a machine language without the written permission of the Chief Executive of P.W.R.I.

この資料は、独立行政法人土木研究所理事長の承認を得て刊行したものである。したがって、本資料の全部又は一部の転載、複製は、独立行政法人土木研究所理事長の文書による承認を得ずしてこれを行ってはならない。