

CALCULATIONS FOR

下  
關  
市  
跳  
開  
橋  
概  
算  
設  
計

紙  
徑  
間  
長  
二  
〇  
〇  
米  
跳  
開  
橋

工  
費  
二  
〇  
二  
〇  
〇  
円

(一〇頁参照)

上

日  
昇  
開  
橋  
(昇  
降  
可  
能)


工  
費  
一  
六  
七  
〇  
〇  
円

(二〇頁参照)

CALCULATIONS FOR

下葉島馬 152 #2-11 橋

Bascule span. 20.0 m. clear.  
width 6.0 m roadway, sidewalks 2.5 m each.  
loading 2nd class loading.



scale 1/150

Roadway floor 7.5 cm wood blocks par  
10 cm planking

Sidewalk floor 5 cm planking

Stringers 250 x 125 @ 38.3 kg

30  
-16.5  
13.5  
2.5  
16

Floor beam  
Dead load.

Roadway.  
pavement 6.5 @ 95 = 62  
planking 10 @ 65 = 65  
maining piece  $\frac{1 \times 15}{8} @ 680 = 12$   
Stringers 40 + 8 = 50  
11  
200 kg/m.  
3.6" @ 200 = 720  
floor beam. 150  
870 kg/m.


Sidewalk.  
planking 5 @ 65 = 3.3  
cross beam. = 20  
stringer 40  
7  
100  
3.6 @ 100 = 360  
120  
480 kg/m.

D.L. m.  $\frac{1}{8} \times 870 \times 6.4^2 = 4460$   
 $\frac{1}{2} \times 480 \times 3^2 = 2160$   
 $100 \times 3 = 300$   
2000 or 2160 kg/m.

CALCULATIONS FOR

(2)  
1/A

Side span 9.0m span. 3 girders 3m c/c.



8 ton truck

$$3000 \times 1.3 = 3900 \text{ kg}$$

$$3900 \times \frac{2.15 + 0.75}{3.0} = 4290 \times 2 = 8580 \text{ kg on center girder}$$

4290 " side


front & rear of trucks

unif load.  $500 \times 3.0 = 1500 \text{ kg/m for center girder}$

$$500 \times 1.5 = 750$$

$$400 \times 2.5 = 1000$$

1750 " side



Side of truck

$$3 \times 500 = 1500 \times \frac{1.5}{3.0} = 750 \times 2 = 1500 \text{ kg on center girder}$$

750

1008. side girder

Live load moment

Center girder.

wheel. rear  $8580 \times \frac{1}{2} = 4290$

front  $2860 \times \frac{1.9}{9} = 290$

$$4580 \times 4.5 = 20600$$

unif. load.

$$1500 \times 3 \times 1.5 = 70$$

$$1500 \times 3.3 \times 7.35 = 36380$$

$$\frac{36450}{9} = 4050 \times 4.5 = 18250$$

$$4950 \times 2.85 = 14100$$

$$\frac{24750}{2} = 12375 \text{ kgm}$$

Side girder

wheel.

$$20600 \div 2 = 10300$$

$$750 \times 3 \times 1.5 = 40$$

$$750 \times 3.3 \times 7.35 = 18200$$

$$\frac{18240}{9} = 2025 \times 4.5 = 9120$$

$$2475 \times 2.85 = 7050$$

$$\frac{1}{8} \times 1000 \times 9 = 112.5$$

$$= \frac{10120}{22490} \text{ kgm}$$

CALCULATIONS FOR

D.L.

Center girder

asphalt block	6.38 cm	c 21 =	6080
cushion	1.2 "	c 17 =	20
slab	15 "	c 24 =	360
			<u>460 x 3.0 = 1380 kg.</u>

Stringer 1 c 40 = 40

floor beam 2000

girder lateral 980

7620  
2400 kg/m

80  
150  
60  
290 x 1.2 = 348

$$M = \frac{1}{8} \times 2400 \times 9^2 = 24,300 \text{ kgm}$$

Side girder

floor roadway 1.5 c 460 = 690

stringer " 40  
2 c 30 = 60  
100

floor beam 2000

girder 400  
180

side walk floor

par. 3.0 c 17 = 50

slab 13. c 24 = 312

360

1900

$$M = \frac{1}{8} \times 1900 \times 9^2 = 19,300 \text{ kgm}$$

Summary


	Center girder	Side girder
D.L.	21,300	19,300
LL	24,800	22,500
	<u>46,100 kgm</u>	<u>41,800 kgm</u>

CALCULATIONS FOR

10

Side span

Center girder section



1 web  $770 \times 9 = 69.3$        $\frac{1}{2}$  web = 8.7 cm

flg' stem =  $\frac{46,100 \times 100}{75} = 61,500$

flg' area =  $\frac{61,500}{1200} = 51.3$   
 $\frac{8.7}{42.6 \text{ net}}$

2C  $100 \times 100 \times 13 = 43,400 - 13 = 30,42$

1 comp.  $220 \times 10 = 2,200 - 5 = 1,700$   
 $\frac{68,42}{47,42 \text{ net}}$

approx. wt. of main gr.

2 flg's @ 65.4 = 131.8

1 web  $9 \times 77 = 69$   
 $\frac{69}{200} @ 785 \times 9.5 = 1,490$

details 40% =  $\frac{610}{2,100}$

Summary for structural steel in # fixed span.

Stringer 2 C40 =  $80 \times 9.5 = 760$

2 C25 =  $50 \times 9.5 = 475$

floor beam 4 C150 = 6,000

lateral br. = 7,500

main girders 3 C210 = 6,300


shaes 4 C250 = 1,000

exp. jt. 2 C100 = 790

17,935 kg call it 18 tons.

CALCULATIONS FOR

下 梁




Clear lead on front & rear of truck

$$\frac{500 \times 2.4 \times 1.2}{3.6} = 400 \text{ kgm}$$

rear wheel

$$3000 \times 1.3 = 3900 \text{ kg}$$



$$\begin{aligned} \text{M. } 7800 \times 2.75 &= 21,450 \\ 3900 \times 1.8 &= -7,000 \end{aligned}$$

$$14,450 \text{ kgms}$$

$$\frac{1}{8} \times 400 \times 6.4^2 = 2050$$

$$16,500 \text{ kgms}$$

neg. m

$$3.6 \text{ cantilever} = 1440 \text{ kgms}$$

$$\frac{1}{2} \times 1440 \times 2.7^2 = -5250 \text{ kgms}$$

Summary

DL  
LL

	moment at center	at support
	2000	-2160
	16500	-5250
	+ 18500 kgms	-7410 kgms

$\text{weld. } 750 \times 9 = 675$        $\frac{1}{8} \text{ web} = 8.45 \text{ cm}^2$   
 $\text{flg. stress} = \frac{18500 \times 100}{70} = 26500 \text{ kg}$   
 $\text{flg. area} = \frac{26500}{1200} = 22.1 \text{ cm}^2$   
 $\quad \quad \quad - 8.5$   
 $\quad \quad \quad \underline{13.6 \text{ cm}^2 \text{ net}}$

$$215 \quad 125 \times 75 \times 9 = 34.3 - 9 = 25.3 \text{ net}$$

Weight of floor beam

$$415 \quad 125 \times 75 \times 9 @ 13.5 \times 6.4 = 346$$

$$\text{web } 750 \times 9 @ 5.30 \times 6.4 = 339$$

$$685$$

$$\text{details } 40\% = 275$$

$$960 \text{ kg}$$

Cantilever area

$$\text{diag. } 960 \times \frac{2.7}{6.4} = 400 \text{ kg}$$

wt. of one complete floor beam

$$\text{center spans } 2 \times 1100 = 800$$

$$\text{center spans } 960$$

$$\underline{1760 \text{ kg}}$$

CALCULATIONS FOR

Main bascule girder  
Dead load

Roadway floor	6.4" @ 200 =	1280
Sidewalk	2.75" = 5.5 @ 100 =	550
hand rails	2 @ 100 =	200
floor beams	176" + 3.6 =	490
Lateral bracing		250
main girder assumed (outside girders)		900
		<u>1770</u>
		3800 kg/m. ÷ 2 = 1900 kg/m for one girder
Outside girders	800 ÷ 2 =	400

Max. D.L. on main girder

$\frac{1}{2} \times 1900 \times 14.7^2 = 205000 \text{ kgm}$   
30% imp. = 61500  
266500 kgm

web  $2000 \times 9 = 180$   $\frac{1}{8}$  web = 22.5  
flg. stress =  $\frac{266500}{193} = 138000 \text{ kg}$   
flg. area =  $\frac{138000}{1200} = 1150$   
 $\frac{1150}{22.5} = 51.1 \text{ cm}^2 \text{ net}$   
3% load on end steel, bolts, lip, flange break etc  $\frac{10.0}{102.5} =$

use  
 $2L^3 \quad 150 \times 150 \times 11 = 64.0 - 11 = 53.00$   
 $2 \text{ compl. } 320 \times 12 = 76.8 - 12 = 64.8$   
 $140.8 \text{ cm}^2 \text{ net} \quad 117.8 \text{ cm}^2 \text{ net}$

Approx. wt. of main girder

main section 2 flanges @ 140.8 = 281.6  
1 web pl. = 180  
461.6  
details say 25%  $\frac{238.4}{700.0 \text{ cm}^2 \text{ net} \times 0.785 = 550 \text{ kg/m}}$   
wt. of one girder =  $22.2" @ 550 = 12200 \text{ kg}$

Outside main girder say 10000 kg


Lateral bracing " 20" @ 250 = 5000

Summary of Structural Steel for Bascule Leaf.

Stringers	7 @ 40 x 22.2 =	6210
"	4 @ 30 " " =	2670
floor beams	7 @ 1760 =	12320
Lateral bracing	5000 } 1000 }	6000
main girder inside	2 @ 12200 =	24400
" outside	2 @ 10000 =	20000
Shims	4 @ 500 =	2000
floor breaks	2 @ 2000 =	4000
		<u>78000 kg</u>

CALCULATIONS FOR

Balancing links



vert. comp. of link pull.

$$4000 \times 22.2 =$$

$$\text{outside guides } 2 \times 10000 =$$

$$\text{racks}$$

$$88800 \text{ kg} \times 11.8 = 1048000$$

$$20000 \times 2.5 = 50000$$

$$2200 \times 2.2 = 5000$$

$$\underline{111000 \text{ kg}} \qquad \underline{1103000 \text{ kgm}}$$

vert. comp. of moving leaf complete

moment abt. transmission

$$\text{vert. comp. of link pull} = \frac{1103000}{8.2} = 134700 \text{ kg}$$

67400 kg for one link

link pull

$$67400 \times \frac{9.5}{8.0} = 80000 \text{ kg}$$

$$30\% \text{ impact} = \frac{24000}{104000 \text{ kg}}$$

$$\text{SR} = \frac{104000}{1200} = 78 \text{ cm} \text{ nut}$$

$$\text{case } 2 \text{ I } 380 \times 100 \times 13 = 171.4 \times \left\{ \frac{20}{100} \right\} = 125.1 \text{ cm nut}$$

$$\text{dpr} = 55 \text{ about}$$

approx. wt. of one link

$$2 \text{ I } 380 \times 100 @ 67.3 \text{ kg} \times 10 = 1380$$


details say 170 kg

$$\frac{950}{2300 \text{ kg. one link}}$$

Counterweight required

$$\text{moment about transmission} = 1103000 \text{ kgm}$$

$$\text{Cwt reqd.} = \frac{1103000}{5.6} = 197000 \text{ kg (全体 = 7)}$$



Volume of cwt. assumed as

$$2.2 \times 3.2 \times 8.0 = 56.3 \text{ m}^3$$

$$\text{density of cwt. concrete} = \frac{197000}{56.3} = 3500 \text{ kg/m}^3 \quad (223 \frac{1}{4})$$

$$7850x + (1-x)2200 = 3500$$

$$0.23 \times 7850 = 1805$$

$$5650x = 1300$$

$$0.77 \times 2200 = \frac{1695}{3500 \text{ kg}}$$

$$x = \frac{1300}{5650} = 0.23$$

$$\text{Total vol. of conc} = 56.3 \times 0.77 = 43.4 \text{ cul m}$$

$$\text{Steel scrap} = 56.3 \times 1805 = 10170 \text{ kg}$$

$$7850x + (1-x)1700 = 3500$$

$$0.293 \times 7850 = 2300$$

$$6150x = 1800$$

$$0.707 \times 1700 = \frac{1200}{3500}$$

$$x = \frac{1800}{6150} = 0.293$$

$$\text{Total vol. of mortar} = 56.3 \times 0.707 = 39.8 \text{ cul m}$$

$$\text{Steel scrap} = 56.3 \times 2300 = 12950 \text{ kg}$$

CALCULATIONS FOR

Balance girders	moment on balance beam link pull own wt. of beam. links wt.	$1103,000 \div 2 = 551,500$ $\frac{1}{2} \times 800 \times 8.2^2 = 26,900$ <u>578,400</u> kgm. $2300 \times 8.2 = 18,900$ <u>597,300</u> kgm.	
		$\frac{30\% \text{ impact}}{20} = \frac{119,700}{717,000}$	one girder.
	flg' stream	$= \frac{717,000}{1.95} = 368,000$	
	flg' area	$= \frac{368,000}{1200} = 307 \text{ cm}^2$	
	1/8 web $200 \times 12 \div 8$	$= \frac{30}{277 \text{ net}}$	
	Case 2C $150 \times 150 \times 19 = 106.8 - 19.0 = 87.8$ 2Pls $230 \times 12 = 15.2 - 12 = 43.2$ 3 cov. pl. $320 \times 19 = 182.0 - 28.5 = 153.5$	<u>344.0</u> net	<u>284.0</u> cm <sup>2</sup> net.
	2 flgs @ 344 = 688 1 web pl. $12 \times 200 = 240$ 928		
	60% details = 557 $148.5 \times 785 \times 15.6 = 18,200 \text{ kg}$		(- 4.5)
Lateral bracing	Diagonals with gusset pl. cross struct. + longi. strut, cut gr.	6,000 <u>14,000</u>	20,000 (全体)
Counterweight tower	ray		<u>23,000</u> kg (全体 = 3)
Summary of structural steel:	bascule leaf complete	78,000	
	balance girders 2@18,200 = 36,400		
	laterals cut gr. etc. <u>2,000</u>	56,400	
	links 2@2300 = 4,600		
	counterweight tower complete	23,000	
	grillage under transmission 2@1500 = 3,000		
	floor beams over bascule pier = 1,500		
		500	
		<u>167,000</u> kg	
	fixed spread	18,000	
		<u>185,000</u> kg or 185 tons.	

CALCULATIONS FOR

20m Bascule span

Estimate of Operating power

Journal friction

$$M_F = \frac{P \cdot f}{100} = \frac{P \cdot f}{200}$$

67400  
28200  
98.000

$$90000 \times \frac{3.6}{8} = 40.000$$

Journals

Journals	Di. D.	Load P	f	
Trink pins	18	80,000	0.15	200 * 4 = 4320
Transmission shaft	18	40,000	'	2 = 1080
Cut "	30	190,000	'	2 = 8,550

13950 kg m

$$\text{Rack force } F_F = \frac{13950}{2.20} = 6350 \text{ kg for 2 racks.}$$

Eccentricity

End reaction assumed as 20500 = 1000 kg

$$\text{moment } 1000 \times 22.5 = 22500 \text{ kgm}$$

$$\text{Rack force } F_E = \frac{22500}{2.20} = 10200 \text{ kg for 2 racks}$$

Wind moment

70 kph wind assumed during operation

$$12.3 \times 22.2 \times 11.8 \times 70^4 = 225500 \text{ kgm}$$

$$\text{Rack force } F_W = \frac{225500}{2.2} = 102500 \text{ kg}$$

Summary of Rack forces

Journal friction  
eccentricity  
inertia  
wind

6350  
10200  
950  
102500  
120000 kg for 2-racks

Time of operation assumed as 60 sec.

$$15 \div 2 = 7.5$$

$$30 = 30.0$$

$$15 \div 2 = 7.5$$

Equivalent time of unif. speed = 45.0 sec

$$\text{Unif. speed at rack circle} = \frac{2\pi \times 2.2 \times 85}{45 \times 360} = 0.0725 \text{ m/sec.}$$

$$\text{Theoretical HP req'd} = \frac{120000 \times 0.0725}{76} = 114.5$$

$$\text{gear efficiency say } (0.94)^7 = 0.648$$

$$\text{Actual HP req'd} = \frac{114.5}{0.648} = 177 \text{ HP} \quad \text{--- } 60 \text{ sec.} \quad 30+15=45$$

$$177 \times \frac{45}{75} = 106 \text{ HP} \quad 90 \text{ sec} \quad 60+15=75$$

$$177 \times \frac{45}{105} = 81 \text{ HP} \quad 120 \text{ sec} \quad 90+15=105$$

- 12.5 m

gear 7 1/2 rack radius = 2.5 m  
rack force 120,000 kg  
2.5 m / 2.5 = 120,000 kg

CALCULATIONS FOR

20m Bascule

Estimate of cost.			
Bascule proper.			
wood block pavement, 22x6.0 =	132 m <sup>2</sup> @ 7.00 =	1920	
10cm plankings #12, 22x6.4 =	141' @ 6.00 =	850	
5" " " 2x3x22 =	132' @ 3.50 =	460	
nailing pieces, copings etc	10 m <sup>3</sup> @ 45.00 =	450	
bolts + nails etc	1.0 ton @ 250 =	250	
cast iron drains 16	16 @ 5.00 =	80	
			3,000
Structural steel (1x272-11 13)	167.00 ton @ 300 =	50,100	
Cut. concrete 1:1.5:3	43.4 m <sup>3</sup> @ 18 =	780	
steel scraps	10.2 ton @ 70 =	715	
reinforcement	1.5' @ 130 =	195	
			1,690
Operating house	木造 900 階段等用等 200 鋼材 400		1,500
	(仕上 等 等)		56,300 円
Mechanical equipments:			3,500 700
Forged steel parts	8.45 ton @ 1800 =	15,200	
Cast steel "	2.75 @ 1300 =	28,300	
Cast iron "	14.95 @ 700 =	10,500	
rolled steel "	7.10 @ 650 =	4,600	
phosphor bronze "	1.65 @ 3300 =	5,400	
	53.90 ton		64,000
Electrical equipments	2-50HP motor @ 2300 = 4600 3-3HP " @ 600 = 1800		6400
Electric wiring complete		3200	9600
			73600
Fixed span.			3,500 10,000
Asphalt block pav. 6.0x9.0 =	56.5 m <sup>2</sup> @ 3.6 =	200	
Cement mortar fin.	50 @ 1.2 =	60	
Slab, concrete	17.5 m <sup>3</sup> @ 15 =	260	
reinf.	2.5 ton @ 130 =	330	
forms. 13.0x10 =	130 m <sup>2</sup> @ 1.5 =	200	
			1,050
Structural steel	18.0 ton @ 240 =	4,300	
			5,400
Handrails 全長 80m @ 100kg =	8.0 ton @ 200 =	1,600	
親柱 日 和 等 欄 一 部	4' @ 1500 =	6,000	
gates	2 48 @ 1000 =	2,400	
			7,600
			2,000
	上部工 計		155,600 円

10  
2  
3  
10

CALCULATIONS FOR

20" Bascule span.

<p>Steel structures Bascule Abutment Floor.</p>	<p>Asphalt blocks pav. <math>6.0 \times 6.5 =</math> Concrete <math>0.20 \times 6.6 \times 6.5 =</math> <math>0.40 \times 0.3 \times 6.6 \times 2 =</math> <math>0.30 \times 0.50 \times 6.6 \times 2 =</math> <math>0.13 \times 2.5 \times 6.6 =</math> <math>0.13 \times 3.6 \times 6.6 =</math> <math>0.25 \times 0.2 \times 6.6 \times 2 =</math></p>	<p><math>39.0 \text{ m}^2 @ 3.6 = 140.</math> <math>8.6</math> <math>1.6</math> <math>2.0</math> <math>2.1</math> <math>3.1</math> <math>0.7</math> <u>1.9</u> <math>20.0 \text{ m}^3 @ 15.0 = 300</math></p>	
<p>abutment body, 12.3 x 13 concrete.</p>	<p>Steel <math>20 \times 125 =</math> forms <math>13 \times 6.6 =</math> walls <math>0.3 \times 2.2 \times 26.3 =</math> <math>0.6 \times 13.3 =</math> col. <math>1.5 \times 2.6 \times 1.5 \times 2 =</math> <math>0.8 \times 2.5 \times 3.5 \times 2 =</math> <math>1.6 \times 2.7 \times 13.5 \times 2 =</math> floor <math>0.20 \times 3.3 \times 13.2 =</math> <math>0.40 \times 0.30 \times 3.3 \times 8 =</math> col. <math>1.6 \times 1.6 \times 2.5 \times 2 =</math> stairs <math>0.7 \times 1.25 \times 2.0 =</math></p>	<p><math>2.5 \text{ ton} @ 130 = 325</math> <math>86 \text{ m}^2 @ 1.5 = 129</math> <u>105</u> <math>17.4</math> <math>8.0</math> <math>11.7</math> <math>14.0</math> <math>116.5</math> <math>8.7</math> <math>3.2</math> <math>1.8</math> <math>1.8</math> <u>6.9</u> <math>190 \text{ m}^3 @ 15.0 = 2850</math> <math>11.5 \text{ ton} @ 120 = 1380</math></p>	<p>1000</p>
<p>Steel forms <math>26.6 \times 16 = 426</math> <math>60 \times 125 = 7500</math> <math>130 \times 50 = 6500</math> <math>140 \text{ m}^2</math></p>	<p>190 @ <math>60 \text{ m}^2 =</math> <math>3.0 \times 4.3 \times 2 = 258</math> <math>13.3 \times 3.3 = 44</math> <math>0.4 \times 3.3 \times 16 = 20</math> <math>1.6 \times 3.6 \times 2 = 11</math> <math>1.5 \times 2.5 \times 2 = 7.5</math> <u>30</u></p>	<p><math>378 \text{ m}^2 @ 1.5 = 567</math></p>	
<p>walls. conc. <math>36 - 28.5 = 7.5</math> <math>112 @ 125 = 14020</math> <math>86 @ 60 = 5160</math> <math>19.2</math></p>	<p><math>4.0 \times 9.0 \times 4.5 \times 2 = 324.0</math> <math>7.5 \times 3.0 \times 2 = 45.0</math> steel forms <math>50 \times 7.5 \times 2 =</math> excav (sinking) sand fill <math>28.5 \times 3.0 \times 2 =</math> conc. sheet piles <math>12 \times 2.5 \times 7.0 \text{ m}</math> 割罫 茶角 Shoes</p>	<p><math>569 \text{ m}^3 @ 15 = 8535</math> <math>20 \text{ ton} @ 130 = 2600</math> <math>750 \text{ m}^2 @ 1.5 = 1125</math> <math>540 \text{ m}^3 @ 5 = 2700</math> <math>171 @ 0.6 = 102.6</math> <math>28 @ 25 = 700</math> <math>50</math> <math>2.5 \text{ ton} @ 240 = 600</math> <u>160</u></p>	<p>19000 <u>20000</u> 2000</p>
<p><math>10 @ 15 = 150</math> <math>1.5 @ 120 = 180</math> <math>16 @ 1.0 = 16</math> <math>180 \div 28 = 6.4</math> <u>19</u></p>		<p><math>378 \text{ m}^2 @ 1.5 = 567</math></p>	

CALCULATIONS FOR

20" Bascule.

Pair between fixed and bascule spans.			
Conc.	shaft	$1.8 \times 3.6 \times 8 = 52 \text{ m}^3 \text{ @ } 15 = 780$	
	steel	$52 \text{ @ } 35 = 1820 \text{ m} \text{ @ } 120 = 230$	
	form	$3.6 \times 20 = 72 \text{ m}^2 \text{ @ } 15 = 110$	
			<u>80</u> 1200
well conc.		$2.2^2 = 3.80$ $2.2 \times 7.2 = 15.84$ $19.64 \times 3.7 = 73$	
		$1.6^2 = 2.0$ $1.6 \times 7.2 = 11.5$ $13.5$ $19.65$ $6.15 \times 4.8 = 30$	
		$3 \times 3 \times 3 \times 1.6 \times 4.8 = 27$ $127 \text{ m}^2 \text{ @ } 15 = 1900$	
	Steel	$7.0 \text{ km} \text{ @ } 130 = 910$	
	form	$2.1 \times 8.5 = 182$ $2.9 \times 8.5 = 246$ $428 \text{ @ } 15 = 640$	
	sand fill	$2.8 \text{ @ } 6 = 170$	
	Excav. (sinking)	$19.65 \times 8.5 = 167 \text{ m}^2 \text{ @ } 5 = 840$	
	shoe	$1.5 \text{ km} \text{ @ } 240 = 360$	
			<u>80</u> 400
			5300
			<u>6500</u> 19 <u>1000</u>
Abutment			
shaft conc.		$0.6 \times 4.0 \times 8.0 = 19.2$ $0.4 \times 5.0 \times 15.0 = 30$ $0.6 \times 7.0 \times 15.0 = 36$	
		$85 \text{ m}^2 \text{ @ } 15 = 1280$	
	steel	$85 \text{ @ } 40 = 3400 \text{ m} \text{ @ } 130 = 460$	
	form	$5 \times 40 = 200 \text{ m}^2 \text{ @ } 15 = 300$	
	granite	$3 \times 3 \times 13 = 117 \text{ @ } 120 = 160$	
			<u>2200</u>
	dwells.		
	conc.	$4 \times 6 \times 4.5 \times 2 = 216$ $8.68 \times 4.5 \times 2 = 60$ $276 \text{ @ } 15 = 4140$	
	Steel	$7.0 \text{ km} \text{ @ } 130 = 900$	
	form	$20 + 16.5 = 36.5 \times 2 \times 9 = 660 \text{ m}^2 \text{ @ } 15 = 990$	
	sand fill	$17.25 \times 4.5 \times 2 = 155$ $100 \text{ @ } 6 = 600$	
	shoes	$2.0 \text{ km} \text{ @ } 240 = 480$	
	Excav. (sinking)	$28 \times 90 \times 2 = 5040 \text{ m}^2 \text{ @ } 5 = 2160$	
		$27 \text{ @ } 600 = 16200$ $28 \text{ @ } 25 = 700$	
	sheet piles		<u>9800</u>
			12000 19 <u>2000</u>
Summary of cost for the entire Bridge			
<del>Sub-structures</del>			
	Bascule Abutment	1 set	22,000
	Pier	1 "	7,500
	Abutment	1 "	14,000
			<u>43,500</u>
Superstructures Complete (see page 7.)			
			<u>15,560</u>
	Total net cost		<u>199,100</u> 19 12 27

CALCULATIONS FOR

下関市彦島町連絡道路跳開橋 (20m clear span)

<p>Estimate of cost. Superstructures:- Bascule proper.</p>	<p>Floor complete Structural steel counterweight complete operating house finishing, and misc. exp.</p>	<p>167.0 tons @ 300 =</p>	<p>3000 50,100 1,700 1,500 700 <u>57,000</u> 17</p>
<p>Fixed span</p>	<p>Floor complete Structural steel</p>	<p>54.0 tons @ 1300 = 2-50 HP motor @ 3300 = 6600 4-1 HP " @ 400 = 1600 1-2 HP " @ 500 = 500 wiring etc. 4900</p>	<p>70,000 <u>13,600</u> 83,600</p>
<p>Handrails</p>	<p>handrails light pedestals.</p>	<p>18.0 tons @ 240 = 8.0 tons @ 200 = 4 sets @ 1500 =</p>	<p>1,100 <u>4,300</u> 5,400 1,600 <u>6,000</u> 7,600</p>
<p>Gates and locking</p>	<p>gates lock</p>	<p>5 sets @ 1000 = Summary =</p>	<p>5,000 <u>158,600</u> 17</p>
<p>Sub structures Bascule abutments.</p>	<p>Roadway floor complete body wells</p>	<p>2 wells @ 7500 =</p>	<p>1,100 5,900 <u>15,000</u> 22,000</p>
<p>Front pier</p>	<p>shaft well</p>	<p>shaft</p>	<p>1,500 <u>6,000</u> 7,500</p>
<p>Abutment</p>	<p>shaft</p>	<p>shaft</p>	<p>2,900 <u>11,100</u> 14,000 <u>43,500</u> 17</p>
<p>Total cost of the entire bridge</p>	<p>158,600 + 43,500 = 202,100 17 Call this <u>202,000</u> 17</p>		

Time of operation 20 sec.  
 Angle of " 90°  
 no. of rev. of rack  $n = \frac{60}{80 \text{ sec}} = 0.75 \text{ rev/min.}$   
 motor speed 1800 rev/min.  
 gear ratio req'd =  $\frac{1800}{0.75} = 2,400$


worm gear	1:30	} 1:2400
Spur "	1:2.8	
" "	1:2.8	
rack & pinion	1:10.	

efficiency of gear train  
 $\eta = 0.50 \times 0.94^3 = 0.415$   
 call this 40%

彦島連続可動柵用遮蓋機

縮尺 1:20

一箇所當り 1500円以内




Gate. 1:20

CALCULATIONS FOR

12

Cross section of bridge



Scale 1:60


$$\frac{650}{8} = 81$$

6.1 cm pavement	c 9.6	= 58.5
10 cm planking	c 6.0	= 60
misc.		1.5
		<u>120 kg/m<sup>2</sup></u>

Dead load moment  $\frac{1}{8} \times 120 \times 81^2 = 8 \text{ kgm}$

motor truck rear wheel	3000
impact 30%	<u>900</u>
	3900 kg

Effective width of planking for one wheel assumed as 60 cm  
load on one meter strip  $3900 \div 6.0 = 6500 \text{ kg}$



live load moment	$3250 \times 405 = 1316$	12.2
	$3250 \times 0.98 = 318$	<u>27</u>
		998 kgm

moment  $\frac{998}{8} = 124.75$   
1006 kgm

Section modulus required  $\frac{1006 \times 100}{70} = 1440 \text{ cm}^3$


section modulus  $\frac{100 \times 10^2}{6} = 1660 \text{ cm}^3$

Stringer

dead load		
pavement & planking	120	
nailing near	$120 \times 1.5 \times 600 = 111$	$250 \times 1.75 = 38.2 \text{ kg}$
	<u>40</u>	<u>52</u>
	171 kg	183 kg

dead load moment  $\frac{1}{8} \times 171 \times 4.2^2 = 377 \text{ kgm}$

$500 \times 81 = 405$








$\frac{1}{2} \times 3900 = 1950$	live load moment	
$\frac{405 \times 90^2}{2 \times 420} = 39$		
<u>1989</u>		
	$1989 \times 2.10 = 4180 \text{ kgm}$	

S.M. required  $\frac{4180 \times 100}{110} = 380 \text{ cm}^3$


CALCULATIONS FOR

13

<p>Floor beam</p> 	$\frac{3900}{3} = 1300 \text{ kg}$ $1300 \times \frac{6}{4.2} = 186$ $\frac{3900}{4.086} \text{ kg}$ $\frac{500 \times 300}{4.2} \times 1.5 = 535 \text{ kg}$ $4.086 \times 4 \times \frac{3.55}{6.50} = 8,920 \text{ kg}$	<p>dead load moment</p> $120 \times 4.2 = 504$ $\frac{63 \times 7 \times 4.2}{6.5} = 285$ <p>own weight</p> $151$ $940 \text{ kg/m}$ $\frac{1}{8} \times 940 \times 6.5^2 = 4,960 \text{ kgm}$
	<p>live load moment</p> $8,920 \times 3.25 = 29,000$ $4,086 \times 2.55 = 10,410$ $4,078 \times 0.75 = 3,060$ $\frac{1}{8} \times 535 \times 6.5^2 = 2,830$ $15,530 \text{ kgm}$ $18,360 \text{ kgm}$	<p>summary</p> $18,360$ $4,960$ $23,320 \text{ kgm}$
	<p>flange stress = <math>\frac{23,320}{\frac{0.704 \times 6.50}{1200}} = 33,200 \text{ kg}</math></p> <p>required section = <math>\frac{33,200 \times 1.5}{1200} = 24.6 \text{ cm}^2</math></p> <p>2L 100 x 75 x 10 = 3350 - 88 = 24.20 cm<sup>2</sup></p>	<p><math>\frac{1}{8}</math> web area <math>\frac{70 \times 9^2}{8} = 7.9 \text{ cm}^2</math></p> <p>2L 100 x 75 = 66</p> <p>70 x 9 = 63</p> <p>129 @ 1785 = 101</p> <p>40% = 40</p> <p>141 100%</p>
<p>Design of main girder</p> 	<p>Dead load</p> <p>live load</p> $400 \times 2.5 = 1,000 \text{ kg}$ $500 \times 3.0 = 1,500 \text{ kg}$	<p>Dead load moment</p> <p>live load moment</p> $\frac{1}{8} \times 1,650 \times 21.0^2 = 9,100 \text{ kgm}$
	<p>moment</p> $\frac{1}{2} \times 18,360 \times 10.5 = 96,400$ $\frac{6120 \times 6.9}{210} \times 10.5 = 2,110$ $\frac{1500 \times 6.3}{210} \times 315 = 1,416 \times 10.5 = 14,860$ $\frac{1500 \times 9.3}{210} \times 16.35 = 10,850 \times 10.5 = 114,000$ $1500 \times 9.3 = 13,950 \times 5.85 = 81,600$ $\frac{1}{8} \times 1,000 \times 21.0^2 = 55,000$ $219,760 \text{ kgm}$ $91,000$ $310,760 \text{ kgm}$ <p><math>\frac{1}{8}</math> web area <math>\frac{180 \times 1.1}{8} = 24.7 \text{ cm}^2</math></p> <p>flange stress <math>\frac{310,760}{1.77} = 175,500</math></p> <p>required section <math>\frac{177,500}{1200} = 148</math></p> <p>1233 cm<sup>2</sup></p>	<p>Dead load moment</p> <p>live load moment</p> <p>moment</p> <p>summary</p> $120 \times 3.25 = 390$ $3.5 \times 63 = 220$ $\frac{1}{2} \times 142 \times 6.5 = 42 = 110$ $100$ $60$ $2070 = 140$ $120 \times 2.75 = 42 = 79$ $550$ $1,650 \text{ kg/m}$ <p>add 150 x 150 x 12 = 69.12 - 12 = 57.12</p> <p>24/ 340 x 12 = 81.6 - 62.0 = 69.6</p> <p>126.72</p>

CALCULATIONS FOR

14



$$\frac{310 \times 24.7}{15.14} = 506$$

$$\frac{310 \times 57.1}{15.14} = 1170$$

main section

1 web pl	1800 x 11	c 155.4	x 21.6	= 3360
4 flange Ls	150 x 150 x 12	c 27.1	x 21.6	= 2340
2 cov pl	340 x 12	c 32.0	x 17.0	= 1090
2 "	340 x 12	c 32.0	x 13.0	= 830

Details

55				7620
40	70			3050 + 190
				10670 11210

$$21340 \text{ kg } 20620$$

Total weight of moving span

pavement + planking	120 x 6.5	x 21.6	= 16850
"	2 c 60 x 2.9	x 21.6	= 7520
stringer	7 c 83	x 21.6	= 9530 3000
"	4 c 50	x 21.6	= 4320
floor beam	6 c 145	x 6.5	= 5160
"	12 c 120	x 27.5	= 3960
lateral	788	x 21.6	= 4920 5400
handrail	2 c 75	x 21.6	= 3240
main girders			22000

$$76900 \text{ say } 77 \text{ tons}$$

for one counter weight

38.5 tons

80

$$38.5 \div 2.4 = \frac{163 \text{ m}^3}{60 \times 1.2} = 2.2 \text{ m}$$

structural steel of moving span  
shafts

$$\frac{50460}{49200} \text{ kg}$$

$$3000 \text{ kg}$$

CALCULATIONS FOR

157

assumed weight of moving span (bridge + machinery) = 30 tons  
moving span + counter weight 160 tons  
Force for acceleration

$$F = \frac{Wa}{0.98}$$

$$= \frac{160,000 \times 0.0126}{0.98}$$

$$= 2060 \text{ kg} \quad \checkmark$$

time of operation

acc	15 sec	
unif	30	mean 45 sec
ret.	15	

mean speed of operation  $\frac{8.5}{45} = 0.189 \text{ m/sec}$

$$a = \frac{0.189}{15} = 0.0126 \text{ m/sec}^2 \quad \checkmark$$

Frictional force of girders + track assumed as 15% of wind load  
wind pressure  $50 \text{ kg/m}^2$   
horizontal pressure =  $1.8 \times 221 \times 50 = 1,990 \text{ kg}$   $\checkmark$

$$F_1 = 1,990 \times 0.15 = 299 \text{ kg} \quad \checkmark$$

journal friction assumed as 15% of applied load

$$F_2 = \frac{160,000 \times 0.15}{10} = \frac{24,000}{10} = 2,400 \text{ kg}$$

Force required for unbalanced load  $10,000 \text{ kg}$

total force

2060	✓
300	✓
24,000	✓
4,000	✓
1,200	✓
26,359 kg	7560 / 6000

$$\frac{7560}{4.5} = \frac{26,359 \times 8.5 \times 60}{4.5} = 85,700 \text{ kgm/min} \quad \checkmark$$

$$\frac{5,000}{4.5} = \frac{10,000 \times 8.5 \times 60}{4.5} = 113,500 \text{ kgm/min}$$

efficiency of gear drum dia assumed as 70 cm circumference 2.20 m

$$\text{RPM} = \frac{85 \times 60}{2.2 \times 4.5} = 515 \quad \checkmark \quad \text{RPM of motor } 1100 \quad \checkmark$$

worm gear  $\frac{1,100}{10} = 110$

spur gear  $\frac{1}{2774} = 3 \text{ set}$



efficiency  $0.7 \times 0.94 \times 0.94 \times 0.94 = 0.581$

Required HP

$\frac{85,700}{45,608 \times 0.581}$	$\frac{32.4}{11.3} \text{ HP}$	$\times \frac{1100}{7160} = 23.9$	$23.9 \times \frac{600}{720} = 25.7$
$\frac{56,600}{45,608 \times 0.581}$	$\frac{21.4}{4.28} \text{ HP}$	$\frac{21.4}{45.3} \text{ HP}$	$\frac{21.4}{47.8} \text{ HP}$

25.78 HP  
53.8 HP

CALCULATIONS FOR

<p>Design of tower, load on one column 40 tons of moving lead &amp; 5 tons acc. Required section = <math>\frac{45,000}{1200} = 37.5 \text{ cm}^2</math></p>		
	 <p>ZB 380x100 @ 54.5 kg sectional area 109 cm<sup>2</sup></p>	
<p>Approximate weight of tower</p>		
front column	4 B 380x100 @ 54.5 x 14.4m = 3,140	
"	7 Pl 500x10 @ 39.3 x 10.4 = 1,132	
rear column	4 B 380x100 @ 54.5 x 13.7 = 2,990	
top beam	4 B 380x100 @ 54.5 x 1.9 = 414	
hor. bracing	12 L 150x150x11 @ 25.1 x 2.1 = 632	
dia. bracing	12 L 150x150x11 @ 25.1 x 2.8 = 844	
sway bracing	4 L 150x150x11 @ 25.1 x 7.1 = 713	
"	4 L 150x150x11 @ 25.1 x 6.8 = 682	
"	4 L 150x150x11 @ 25.1 x 6.0 = 602	
"	4 L 150x100x9 @ 17.1 x 6.0 = 410	
top strut	2 L 300x100 @ 46.8 x 7.4 = 693	
		17,252 kg
Details & rivet 85%		5,548 7350
		17,800 kgo 19,610 1/2 (81)
<p>Operating house</p>		
	4 B 300x100 @ 46.8 x 5.5 = 1,030	
	4 B 300x90 @ 38.1 x 5.0 = 762	
	<del>4 L 150x150x11 @ 25.1 x 2.4 = 241</del>	
	2 L 150x150x11 @ 25.1 x 1.5 = 75	
	4 B 300x100 @ 46.8 x 9.6 = 1,808	
	4 L 150x150x11 @ 25.1 x 9.6 = 463	
		4,871
Details & rivet 80%		2,429 1900
Tower		7,300 kg 8,770
		17,800 19,610
		25,100 kg 28,370 1/2 (81)
		summary
		17,800 19,610
		25,100 28,370
		42,900 kgo 48,000
<p>Structural steel of side span</p>		
	 <p>main girder</p>	
	4 L 150x150x12 @ 27.1 x 9.50 = 1,030	
	2 Pl 340 x 12 @ 32.0 x 9.50 = 608	
	1 Web 770 x 9 @ 54.4 x 9.50 = 517	
		2,155
details & rivet head 85%		715 765
		2,870 kg
<p>structural steel of one span</p>		
	<p>main girder 3 @ <math>\frac{3020}{2870} = 8,610</math></p> <p>stringer 2 @ 53 x 9.5 = 1,010</p> <p>" 4 @ 50 x 9.5 = 1,900</p> <p>floor beam 4 @ 145 x 6.5 = 3,780</p> <p>" 8 @ 120 x 2.75 = 2,640</p> <p>lateral 250 200 x 9.5 = 1,900 2380</p> <p>shoe</p>	<p>for 2 spans</p> <p>42,000 kgo</p> <p>47,000</p>
		19,840 kg 20,770
		1,160 1,230
		21,000 kgo 22,000

CALCULATIONS FOR

structural steel for side span  
for 2 spans 42,000 kg  
handrail  $40750 \times 7.5 = 2850 \text{ kg}$   
100

Total weight of structural steel

moving span	49,240 kg	50,500 ✓
shoe	3,000 kg	3,000 ✓
towers	42,900 kg	48,000 ✓
side span	42,000 kg	44,000 ✓
floor break	4,000 kg	8,000 ✓
gate		2,000 ✓
Ciuit girder		11,000 ✓
handrail		2,850 ✓
moving span	3,700	4,400 ✓
fixed span	2,850	3,700 ✓
	6,090 kg	8,100 kg ✓

gate I  $4058 \times 175 = 290$   
11  $175 = 140$   
2010  $\times 60 = 120$   
55

Ciuit girder

2 PL	3000 $\times 9$	c	2127 $\times 6.00 = 2,550$
4 L	150 $\times 150 \times 11$	c	25.1 $\times 6.00 = 600$
4 L	"	c	25.1 $\times 1.00 = 100$
2 PLs	3000 $\times 9$	c	212 $\times 1.00 = 424$
			3,674
details & rivet head	50 %		1,826
			5,500

Total weight of structural steel

moving span	50,500 kg	✓
shoe	3,000	✓
towers	48,000	✓
side span	2022,000 = 44,000	✓
floor break	8,000	✓
gate	2,000	✓
Ciuit girder	11,000	✓
	166,500 kg	166.5 tons ✓

handrail casting

moving span	4,400 kg	✓
fixed span	3,700	✓
	8,100 kg	8.1 tons ✓

CALCULATIONS FOR

16

Pavement

Fixed span roadway asphalt block pavement  
 $2 \times 6.06 \times 9.60 = 116 \text{ m}^2$   
 Sidewalk cement mortar finish  
 $4 \times 2.50 \times 9.60 = 96 \text{ m}^2$

moving span roadway wood block pavement  
 $1 \times 6.06 \times 2.22 = 133 \text{ m}^2$

Concrete slab

Fixed span (roadway 15cm, sidewalk 10cm thick)  
 $2 \times 12.5 \times 9.60 = 240 \text{ m}^3$


Planking

moving span (roadway 10cm, sidewalk 5cm thick)  
 $1 \times 12.5 \times 2.22 = 27.8 \text{ m}^3$

concrete floor for machinery + operating room (20cm thick)  
 $1 \times 0.2 \times 3.5 \times 9.5 = 6.7 \text{ m}^3$

(19)

Cut Sheave



a  $4.5 \times 210 \times 124 \times 3.14 = 36,800$

b  $12 \times 120 \times 25 \times 45 = 16,200$

c  $6 \times 26 \times 25 \times 45 = 17,600$

d  $13.5^2 \times \pi \times 44 = 25,200$

e  $6.0^2 \times \pi \times 44 = 5,000$

$90,800 \times 0.00786$

$= 714 \text{ kg} - 47$

118

832

length of wire rope

4 c 20mmφ - 34 meters long

8 c 30mmφ - 18 meters long

CALCULATIONS FOR

下関市 20m lift Bridge

(20)

Estimate of Cost.  
Super structures:-  
lift span proper

Floor complete. 3000  
 structural steel 123 ton @ 300 = 36900  
 counterweight complete 2 @ 400 = 800  
 operating house 1500  
 finishing and misc expenses = 800  
 43000 円

Mechanical equipment. 30 ton @ 1300 = 39000  
 electrical 3-20HP motor @ 2500 = 7500 (-台設備)  
 gates 2-2HP @ 500 = 1000  
 locks 1-3HP @ 700 = 700  
 wiring cable 2 re 3500  
 3000  
 15700  
 54700 円

Fixed spans. Floor complete 2 @ 1200 = 2400  
 structural steel 44 ton @ 240 = 10600  
 13000

Handrails Handrails 8 ton @ 200 = 1600  
 light pedestals 4 sets @ 1500 = 6000

gates and locking 3 sets @ 1500 = 4500  
 200

123000 円

Sub structures  
piers  
abutments

2 @ 8000 = 16000  
 2 @ 14000 = 28000

44000

Total cost of the entire bridge 123000 + 44000 = 167000 円

Copyright © (2004) by P.W.R.I.

All rights reserved. No part of this book may be reproduced by any means, nor transmitted, nor translated into a machine language without the written permission of the Chief Executive of P.W.R.I.

この資料は、独立行政法人土木研究所理事長の承認を得て刊行したものである。したがって、本資料の全部又は一部の転載、複製は、独立行政法人土木研究所理事長の文書による承認を得ずしてこれを行ってはならない。